

SEATBELT RETROFIT GUIDE

Seatbelt Assy Part No.: 130202-00241BC

-Note: Kit comes with all necessary parts to mount the seatbelt assembly



Harness Adapters

When required, harness adapters are available:

3 PIN MALE CONN ASSY- 5 PACK	310207-BC4527
3 PIN FEMALE CONN ASSY -5 PACK	310207-BC4528



Part Number: 310207-BC4527



Part Number: 310207-BC4528

SEATBELT RETROFIT INSTRUCTIONS

DAEWON SEATS

*This is a **DIRECT REPLACEMENT** warranty*

NOTE: Daewon Seat retrofit procedure will require the retractor covers to be discarded, the locating pin to be cut-off, and the installation of long-bolt and 2 ea. washers present in the kit.

NOTE: All parts in the kit will be utilized for Daewon Seat Retrofit.

NOTE: If the seatbelt is not oriented to approx. 30° of rotation as pictured, it will not extend.



Figure 1: Buckle-Side Assembly



Figure 2: Retractor-Side Assembly

1. Remove lower seat cushion, adjustment lever, and both covers.
 - a. The cover on the retractor side (**Figure 2**) may be cut as shown and discarded (**Figure 3**).
 - b. Retain the buckle-side cover (**Figure 1**) as it is required upon assembly.



Figure 3: Cut Retractor-Side Cover



Figure 4: Alignment tab on Retractor



Figure 5: Locator Pin must be cut



Figure 6: Cut Pin at first shoulder

2. Cut locating pin at first shoulder as pictured (**Figure 5**, **Figure 6**).
3. Replace existing bolt with long bolt from kit, install 2 ea. washers (**Figure 6**).
4. Install new retractor assembly.
 - a. Ensure alignment notch is engaged (**Figure 4**).
5. Remove and replace buckle assembly.
 - a. Route wires as shown (**Figure 1**) or damage will occur.
6. Re-install Buckle-Side cover.

SEARS SEATS

*This is a **DIRECT REPLACEMENT** warranty*

NOTE: No hardware in kit is necessary for Sears Seat Retrofit.

NOTE: If the seatbelt is not oriented to approx. 30° of rotation as pictured, it will not extend.



1. Remove existing retractor and buckle assembly
2. Install new retractor and buckle assembly.